

Cartridge Heater

PROPERTIES	UNITS	STANDARDS	AVERAGE VALUES
Maximum voltage	V	JB/T 2379- 93	480
Maximum watt density	W/cm ²	JB/T 2379- 93	45
Wattage tolerances	%	JB/T 2379- 93	+5 , -10
Resistance tolerance	%	JB/T 2379- 93	+10, -5
Diameter range	mm	JB/T 2379- 93	3mm-40mm
Diameter tolerance	mm	JB/T 2379- 93	± 0.1
Insulation resistance (cold)	MΩ	JB/T 2379- 93	+∞
Insulation resistance (hot)	MΩ	JB/T 2379- 93	≥ 20
Maximum leakage current	mA	JB/T 2379- 93	≤ 0.5
Maximum heating temperature	°C	JB/T 2379- 93	760

TYPICAL APPLICATIONS

Tool heating for e.g. plastic- rubber-, wood- and paper industry
 Equipment for medical technical and laboratory industry
 Braking systems Foundries
 Metal mold, die and platen heating

LIMITATIONS

This products should not be used in a highly corrosive environment.

HEALTH AND ENVIRONMENTAL INFORMATION/HANDLING PRECAUTIONS

Product safety information required for safe use is not included.
 Before handling, read product and safety data sheets and container labels for safe use.

LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Witsto's products are safe, effective, and fully satisfactory for intended end use.

WITSTO SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. WITSTO DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Drawing up date : 2018/04

Revision Index :

WITSTO-CH-11-PACK TECHNIQUE version
 4/10/18